


Plastic Extruders Limited

Russell Gardens, Wickford, Essex, SS11 8DN England

Tel: + 44 (0)1268 577800 Fax: + 44 (0)1268 560027

Sales Tel: + 44 (0)1268 571116

www.plastex.co.uk e-mail: info@plastex.co.uk



January 2009

Grip Rock. – installation and cleaning information.

Installation;

Lay out mat on a clean, dry floor.

If obstructions exist (i.e. table legs, doorways, etc.) cut the mat to fit my marking mat, then cutting on the back with a sharp utility knife.

Do not cover “irregular” floor surfaces— especially floor drains!

Cleaning-

Griprock will last for years, providing it is cared for properly, on a daily basis.

Mats can be easily rolled up (rough surface on the outside to prevent curling), and moved to a location suitable for cleaning.

1. Use water and a mild detergent.
Do not use Bleach (Sodium hypochlorite solution, formula NaClO)
2. Deck brush both sides of mat.
3. Rinse with clean water while brushing.
4. Dry thoroughly

-or-

The following alternate methods have proved successful;

Steam cleaning

Medium pressure washing

Passing it through a large dishwasher

It is important after cleaning to thoroughly rinse the mat and hang it while both the mat *and floor* dry. (*Do not place on wet floor*)



ASSOCIATED CO:
Plastex Matting Inc.
P.O. Box 270
Valley Head
Alabama 35989, USA



Certificate No. GB93/2034

Registered
in England
No. 745566